

Page 1/10

### Safety data sheet according to 1907/2006/EC, Article 31

Version number 3 Printing date 02.07.2024 Revision: 02.07.2024

## SECTION 1: Identification of the substance/mixture and of the company undertaking

- · 1.1 Product identifier
  - · Trade name: iBOND Ceramic Primer
- · 1.2 Relevant identified uses of the substance or mixture and uses advised against No further relevant information available.
  - · **Application of the substance / the mixture** Auxiliary for manufacture of dental prothesis
- · 1.3 Details of the supplier of the safety data sheet
  - Manufacturer/Supplier:

Kulzer GmbH

Leipziger Straße 2, 63450 Hanau (Germany)

Tel.: +49 (0)800 4372522

- · Informing department: E-Mail: msds@kulzer-dental.com
- 1.4 Emergency telephone number: Emergency CONTACT (24-Hour-Number): +49 (0)6132-84463

#### SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
  - Classification according to Regulation (EC) No 1272/2008

Flam. Liq. 2 H225 Highly flammable liquid and vapour.

Eye Irrit. 2 H319 Causes serious eye irritation.

STOT SE 3 H336 May cause drowsiness or dizziness.

- · 2.2 Label elements
  - Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the GB CLP regulation.

· Hazard pictograms





GHS02 GHS07

- · Signal word Danger
- · Hazard-determining components of labelling:

propan-2-ol

Hazard statements

H225 Highly flammable liquid and vapour. H319 Causes serious eve irritation. H336 May cause drowsiness or dizziness.

Precautionary statements

Keep away from heat, hot surfaces, sparks, open flames and other ignition P210

sources. No smoking.

P261 Avoid breathing mist/vapours/spray.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin

with water [or shower].

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact

lenses, if present and easy to do. Continue rinsing.

P337+P313 If eye irritation persists: Get medical advice/attention.

(Contd. on page 2)



Page 2/10

# Safety data sheet according to 1907/2006/EC, Article 31

Printing date 02.07.2024 Version number 3 Revision: 02.07.2024

# Trade name: iBOND Ceramic Primer

(Contd. of page 1)

#### · Additional information:

Contains methyl methacrylate. May produce an allergic reaction.

Product contains: Reportable explosives precursors. Making available, introduction, possession and use according to Regulation (EU) 2019/1148, Article 9.

#### · 2.3 Other hazards -

- · Results of PBT and vPvB assessment
  - · **PBT:** Not applicable. · **vPvB:** Not applicable.

# SECTION 3: Composition/information on ingredients

- · 3.2 Mixtures
  - · Description: -

· Dangerous components:		
CAS: 67-63-0 EINECS: 200-661-7 Index number: 603-117-00-0	propan-2-ol Flam. Liq. 2, H225 Eye Irrit. 2, H319; STOT SE 3, H336	75-90%
CAS: 67-64-1 EINECS: 200-662-2 Index number: 606-001-00-8 Reg.nr.: 01-2119471330-49-xxxx	acetone Flam. Liq. 2, H225 Eye Irrit. 2, H319; STOT SE 3, H336 EUH066	≥5-<10%
CAS: 80-62-6 EINECS: 201-297-1 Index number: 607-035-00-6	methyl methacrylate Flam. Liq. 2, H225 Skin Irrit. 2, H315; Skin Sens. 1, H317; STOT SE 3, H335	≥0.1-<1%

<sup>·</sup> Additional information For the wording of the listed hazard phrases refer to section 16.

#### SECTION 4: First aid measures

- · 4.1 Description of first aid measures
  - · After inhalation Supply fresh air; consult doctor in case of symptoms.
  - After skin contact The product is not skin irritating.
  - · After eve contact

Rinse opened eye for several minutes under running water. If symptoms persist, consult doctor.

After swallowing

Rinse out mouth and then drink plenty of water.

In case of persistent symptoms consult doctor.

4.2 Most important symptoms and effects, both acute and delayed

No further relevant information available.

· 4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

## SECTION 5: Firefighting measures

- · 5.1 Extinguishing media
  - · Suitable extinguishing agents

CO2, extinguishing powder or water jet. Fight larger fires with water jet or alcohol-resistant foam.

(Contd. on page 3)



Page 3/10

# Safety data sheet according to 1907/2006/EC, Article 31

Printing date 02.07.2024 Version number 3 Revision: 02.07.2024

# Trade name: iBOND Ceramic Primer

(Contd. of page 2)

· 5.2 Special hazards arising from the substance or mixture

Can form explosive gas-air mixtures.

Formation of toxic gases is possible during heating or in case of fire.

- 5.3 Advice for firefighters
  - · Protective equipment: No special measures required.
  - · Additional information -

#### SECTION 6: Accidental release measures

- 6.1 Personal precautions, protective equipment and emergency procedures Wear protective equipment. Keep unprotected persons away.
- 6.2 Environmental precautions:

Prevent material from reaching sewage system, holes and cellars.

Dilute with much water.

· 6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (diatomite, universal binders, for small amounts tissues).

Ensure adequate ventilation.

6.4 Reference to other sections

No dangerous materials are released.

See Section 8 for information on personal protection equipment.

\_

### **SECTION 7: Handling and storage**

- · 7.1 Precautions for safe handling Keep containers tightly sealed.
  - Information about protection against explosions and fires:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

- · 7.2 Conditions for safe storage, including any incompatibilities
  - Storage
    - · Requirements to be met by storerooms and containers: Store in cool location.
    - Information about storage in one common storage facility: Not required.
    - Further information about storage conditions:

Store in cool, dry conditions in well sealed containers.

· 7.3 Specific end use(s) No further relevant information available.

#### SECTION 8: Exposure controls/personal protection

· 8.1 Control parameters

67-63-0 propan-2-ol		
WEL (Great Britain)	Short-term value: 1250 mg/m³, 500 ppm Long-term value: 999 mg/m³, 400 ppm	
67-64-1 acetone	·	
WEL (Great Britain)	Short-term value: 3620 mg/m³, 1500 ppm Long-term value: 1210 mg/m³, 500 ppm	
	•	(Contd. on page

\_\_\_ G



Page 4/10

# Safety data sheet according to 1907/2006/EC, Article 31

Printing date 02.07.2024 Version number 3 Revision: 02.07.2024

Trade name: iBOND Ceramic Primer

IOFI V (Fi	ıropean Union) Long-tern	n value: 1210 n	(Contd. of p.
· DNI	, , ,		.g, 000 pp
	ropan-2-ol		
Oral	general population, long	term, systemic	26 mg/Kg (not defined)
Dermal	worker industrial, long te	-	888 mg/Kg/d (not defined)
	general population, long	-	,
Inhalative	worker industrial, long te	rm, systemic	500 mg/m3 (not defined)
	general population, long	term, systemic	89 mg/m3 (not defined)
67-64-1 ad	cetone		
Oral	general population, long	term, systemic	62 mg/Kg (not defined)
Dermal	worker industrial, long te	rm, systemic	186 mg/Kg/d (not defined)
	general population, long term, systemic 62 mg/Kg/d (not defined)		
Inhalative	worker industrial, long te	rm, systemic	1,210 mg/m3 (not defined)
	worker industrial, long te	rm, local	2,420 mg/m3 (not defined)
	general population, long term, systemic 200 mg/m3 (not defined)		
· PNI	ECs		
67-63-0 pi	ropan-2-ol		
freshwater	r	140.9 mg/l (no	t defined)
marine wa	ter	140.9 mg/l (no	t defined)
sewage tre	eatment plant	2,251 mg/l (no	t defined)
sediment, dry weight, freshwater 552 mg		552 mg/Kg (nd	ot defined)
sediment, dry weight, marine water		552 mg/Kg (no	ot defined)
soil, dry weight 28 mg/Kg (not o		28 mg/Kg (not	defined)
67-64-1 ad			
freshwater 10.6 mg/l (not		- '	
marine wa		1.06 mg/l (rabbit)	
-	eatment plant	19.5 mg/l (not defined)	
sediment, dry weight, freshwater 30.4 mg/Kg (not defined)			
sediment, dry weight, marine water 3.04 mg/Kg			· · · · · · · · · · · · · · · · · · ·
soil, dry weight 0.112 mg/Kg (not defined)			

<sup>·</sup> Additional information: The lists that were valid during the compilation were used as basis.

#### · 8.2 Exposure controls

- · Appropriate engineering controls No further data; see section 7.
- Appropriate engineering controls No further data; see section 7.
   Individual protection measures, such as personal protective equipment
   General protective and hygienic measures
   Avoid contact with the eyes.
   Keep away from foodstuffs, beverages and food.
   Instantly remove any soiled and impregnated garments.
   Wash hands during breaks and at the end of the work.
   Avoid contact with the eyes and skin.

(Contd. on page 5)



Page 5/10

# Safety data sheet according to 1907/2006/EC, Article 31

Printing date 02.07.2024 Version number 3 Revision: 02.07.2024

# Trade name: iBOND Ceramic Primer

(Contd. of page 4)

Breathing equipment:

Not neccessary with efficient local exhaust. If exposition to vapours is possible, use breathing protective mask (filter A).

· Hand protection

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

Check protective gloves prior to each use for their proper condition.

recommended

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Penetration time of glove material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

· For the permanent contact of a maximum of 15 minutes gloves made of the following materials are suitable:

Not determined

Butyl rubber, BR Nitrile rubber, NBR

Eye/face protection

Protective goggles are recommended.

Tightly sealed safety glasses.

Body protection: Light weight protective clothing

#### SECTION 9: Physical and chemical properties

# 9.1 Information on basic physical and chemical properties

**General Information** 

Physical state
Colour:
Smell:
Odour threshold:
Fluid
Colourless
Alcohol-like
Not determined.

Melting point/freezing point:

Boiling point or initial boiling point and boiling range 55

boiling range 55 °C
Flammability Not applicable.

· Lower and upper explosion limit

Lower:
Upper:
12.0 Vol %
12.0 Vol %
Flash point:
Auto-ignition temperature:
Decomposition temperature:
Not determined.

SADT Not determined.

(Contd. on page 6)



Page 6/10

# Safety data sheet according to 1907/2006/EC, Article 31

Printing date 02.07.2024 Version number 3 Revision: 02.07.2024

# Trade name: iBOND Ceramic Primer

(Contd. of page 5) · Viscosity: Kinematic viscosity Not determined. · Kinematic viscosity dynamic: Not determined. Solubility · Water: Fully miscible · Partition coefficient n-octanol/water (log value) Not determined. Steam pressure at 20 °C: 48 hPa Vapour pressure: Density and/or relative density Density at 20 °C 0.800 g/cm<sup>3</sup> · Relative density Not determined. · Vapour density Not determined. · 9.2 Other information No further relevant information available. · Appearance: Fluid Form: · Important information on protection of health and environment, and on safety. Self-inflammability: Product is not selfigniting. · Explosive properties: Product is not explosive. However, formation of explosive air/vapour mixtures is possible. · Change in condition Evaporation rate Not determined. · Information with regard to physical hazard classes **Explosives** Void Flammable gases Void · Aerosols Void Oxidising gases
Gases under pressure Void Void · Flammable liquids Highly flammable liquid and vapour. Flammable solids Void · Self-reactive substances and mixtures Void · Pyrophoric liquids Void Pyrophoric solids Void · Self-heating substances and mixtures Void Substances and mixtures, which emit flammable gases in contact with water Void · Oxidising liquids Void · Oxidising solids Void · Organic peroxides Void Corrosive to metals Void · Desensitised explosives Void

GB



Page 7/10

# Safety data sheet according to 1907/2006/EC, Article 31

Printing date 02.07.2024 Version number 3 Revision: 02.07.2024

Trade name: iBOND Ceramic Primer

(Contd. of page 6)

### SECTION 10: Stability and reactivity

- · 10.1 Reactivity No further relevant information available.
- · 10.2 Chemical stability
  - · Conditions to be avoided: No decomposition if used and stored according to specifications.
- · 10.3 Possibility of hazardous reactions No dangerous reactions known
- · 10.4 Conditions to avoid No further relevant information available.
- · 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products: None

### **SECTION 11: Toxicological information**

- · 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008
  - Acute toxicity Based on available data, the classification criteria are not met.

· LD/	LD/LC50 values that are relevant for classification:		
67-63-0 pi	67-63-0 propan-2-ol		
Oral	LD50	5,840 mg/kg (rat) (OECD 401)	
Dermal	LD50	>12,800 mg/kg (rabbit) (OECD 402)	
Inhalative	LC0	≥10,000 ppm /6h (rat) (OECD 403)	
67-64-1 acetone			
Oral	LD50	5,800 mg/kg (rat)	
Dermal	LD50	>15,800 mg/kg (rabbit)	
Inhalative	LC50/4 h	76 mg/l (rat)	

- · Skin corrosion/irritation Based on available data, the classification criteria are not met.
- · Serious eye damage/irritation
- Causes serious eye irritation.
- · Respiratory or skin sensitisation Based on available data, the classification criteria are not met.
- Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.
- Reproductive toxicity Based on available data, the classification criteria are not met.
- STOT-single exposure

May cause drowsiness or dizziness.

- · STOT-repeated exposure Based on available data, the classification criteria are not met.
- Aspiration hazard Based on available data, the classification criteria are not met.
- · 11.2 Information on other hazards
  - · Endocrine disrupting properties

128-37-0 2,6-di-tert-butyl-p-cresol

List II

# **SECTION 12: Ecological information**

- · 12.1 Toxicity
  - · Aquatic toxicity:

67-63-0 propan-2-ol

LC50/96h | 9,640 mg/l (fish) (OECD 203)

(Contd. on page 8)



Page 8/10

# Safety data sheet according to 1907/2006/EC, Article 31

Printing date 02.07.2024 Version number 3 Revision: 02.07.2024

### Trade name: iBOND Ceramic Primer

		(0 11 5 =)
1.050/0//		(Contd. of page 7)
LC50/24h >10,000	0 mg/L (daphnia) (OECD 202)	
67-64-1 acetone		
EC50/48h 8,800 n	ng/l (daphnia)	
	ng/l (fish) (OECD 203)	
· 12.2 Persistence and degradability		
67-63-0 propan-2-	·ol	
Biodegradation 53 % /5d (not defined) (EU C.5)		
67-64-1 acetone		
Biodegradation 90	0.9 % /28d (not defined) (OECD 301D)	
42.2 Bioggovernula	tive notantial No further relevant information ave	silabla

- · 12.3 Bioaccumulative potential No further relevant information available.
- **12.4 Mobility in soil** No further relevant information available.
- · 12.5 Results of PBT and vPvB assessment
  - · PBT: Not applicable.
  - · vPvB: Not applicable.
- 12.6 Endocrine disrupting properties

For information on endocrine disrupting properties see section 11.

- · 12.7 Other adverse effects
  - · Additional ecological information:
    - · General notes:

Do not allow undiluted product or large quantities of it to reach ground water, water bodies or sewage system.

#### SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
  - Recommendation

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

- · Waste disposal key number: 55503
- · Uncleaned packagings:
  - · Recommendation: Disposal must be made according to official regulations.
  - · Recommended cleaning agent: Water, if necessary with cleaning agent.

SECTION 14: Transport information		
14.1 UN number or ID number ADR, IMDG, IATA	UN1993	
· 14.2 UN proper shipping name · ADR	1993 FLAMMABLE LIQUID, N.O.S., special provision 640D (ISOPROPANOL (ISOPROPYL ALCOHOL), ACETONE)	
· IMDG, IATA	FLAMMABLE LIQUID, N.O.S. (ISOPROPANOL (ISOPROPYL ALCOHOL), ACETONE)	

(Contd. on page 9)



Page 9/10

# Safety data sheet according to 1907/2006/EC, Article 31

Printing date 02.07.2024 Version number 3 Revision: 02.07.2024

### Trade name: iBOND Ceramic Primer

(Contd. of page 8) · 14.3 Transport hazard class(es) · ADR · Class 3 (F1) Flammable liquids. · Label · IMDG, IATA · Class 3 Flammable liquids. · Label 14.4 Packing group ADR, IMDG, IATA II· 14.5 Environmental hazards: Marine pollutant: No · 14.6 Special precautions for user Warning: Flammable liquids. Kemler Number: *3*3 F-E,<u>S-E</u> · EMS Number: · Stowage Category · 14.7 Maritime transport in bulk according to IMO instruments Not applicable. · Transport/Additional information: · ADR · Limited quantities (LQ) 1L · Excepted quantities (ÉQ) Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml · Transport category D/E · Tunnel restriction code ·IMDG Limited quantities (LQ) 1L (Contd. on page 10)



Page 10/10

## Safety data sheet according to 1907/2006/EC, Article 31

Version number 3 Revision: 02.07.2024 Printing date 02.07.2024

### Trade name: iBOND Ceramic Primer

	(Contd. of page 9)
· Excepted quantities (EQ)	Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml
· UN "Model Regulation":	UN 1993 FLAMMABLE LIQUID, N.O.S., SPECIAL PROVISION 640D (ISOPROPANOL (ISOPROPYL ALCOHOL), ACETONE), 3, II

## SECTION 15: Regulatory information

- 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- No further relevant information available.
- · 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

#### **SECTION 16: Other information**

These data are based on our present knowledge. However, they shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Relevant phrases

H225 Highly flammable liquid and vapour.

Causes skin irritation. H315

H317 May cause an allergic skin reaction.

H319 Causes serious eye irritation.

H335 May cause respiratory irritation.

H336 May cause drowsiness or dizziness.

EUH066 Repeated exposure may cause skin dryness or cracking.

#### Abbreviations and acronyms:

SADT: Self Accelerating Decomposition Temperature

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the

International Carriage of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods

IMDG: International Maritime Code for Dangerous Goods
IATA: International Air Transport Association
GHS: Globally Harmonised System of Classification and Labelling of Chemicals
EINECS: European Inventory of Existing Commercial Chemical Substances
ELINCS: European List of Notified Chemical Substances
CAS: Chemical Abstracts Service (division of the American Chemical Society)
DNEL: Derived No-Effect Level (UK REACH)
PNEC: Predicted No-Effect Concentration (UK REACH)
LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

PB1: Persistent, Bioaccumulative and Toxic
vPvB: very Persistent and very Bioaccumulative
Flam. Liq. 2: Flammable liquids – Category 2
Skin Irrit. 2: Skin corrosion/irritation – Category 2
Eye Irrit. 2: Serious eye damage/eye irritation – Category 2
Skin Sens. 1: Skin sensitisation – Category 1
STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

\* Data compared to the previous version altered.